

## DECLARATION OF PERFORMANCE (DoP)

N° 1025-CPR-2013-07-01



1. Unique identification code of the product type:

### POLIISO EXTRA

**Polyisocyanurate (PIR) Panels – Polyiso foam expanded between two substrates of multilayer aluminum**

 2. Intended use of the product: **Thermal insulation for construction**

3. Name and Address of the Manufacturer:

**EDILTEC INSULATION S.p.A.**
**Z.I. CONTRADA STAMPALONE – 64036 – CELLINO ATTANASIO (TE)**
**Tel. 0861 668008 – Fax. 0861 669256**

 4. System for the evaluation and verification of the constancy of performance: **System 3**

5. Notified Bodies:

**ISTITUTO GIORDANO, Via Rossini, 2 – 47814 Bellaria (RN) – ITALY, NB 0407**
**CEIS S.L., carretera Villaviciosa de Odón in Móstoles Km 1.5 – 28935 Móstoles (Madrid) - SPAIN, NB 1722**
**L.S.FIRE TESTING INSTITUTE S.R.L., via della Bonifica, 4 -64010 Controguerra (TE) – ITALY, NB 2479**

**Notified testing laboratories (NB 0407 - NB 1722 - NB 2479) which have carried out type tests (ITT) for product groups according to characteristic.**


❖ The performance of the product referred to in point 1 is in accordance with the performance declared in point 6.

❖ This declaration of performance is issued. under the sole responsibility of the manufacturer referred to in point 3.

6. Declared performance

Essential Feature	Performance	Harmonised Technical Specification
<b>Thickness tolerance</b>	Thickness < 50 mm :	EN 13165:2016
	Thickness 50 – 75 mm :	
	Thickness > 75 mm :	
<b>Length and width tolerance</b>	Size < 1000 mm :	EN 13165:2016
	Size from 1000 mm to 2000 mm :	
	Dimensions from 2001 mm to 4000 mm :	
	Size > 4000 mm :	
<b>Dimensional stability under specific temperature and humidity conditions</b>	<b>Declared Class: DS(70,90)4</b> At 70° C and 90% R.H.: Length-width change: ≤ 1% Thickness Change: ≤ 4%	

pag. 1/2


**6. Declared service:**

(N° 1025-CPR-2013-07-01)

Essential Features	Performance			Harmonised Technical Specification
<b>Thermal Conductivity (<math>\lambda</math>D) and Thermal Resistance (RD)</b>	<b>Thickness [mm]</b>	<b><math>\lambda</math>D: [W/mK]</b>	<b>RD: [m2K/W]</b>	
	20	0,022	0,90	
	30	0,022	1,35	
	40	0,022	1,80	
	50	0,022	2,25	
	60	0,022	2,70	
	70	0,022	3,15	
	80	0,022	3,60	
	90	0,022	4,05	
	100	0,022	4,50	
	120	0,022	5,45	
	140	0,022	6,35	
	160	0,022	7,25	
<b>Compressive strength with 10% crushing</b>	<b>Declared level: CS(10/Y)150</b> ≥ 150 kPa			EN 13165:2016
<b>Determination of compressive viscous creep</b>	<b>NPD</b>			
<b>Perpendicular tensile strength</b>	<b>NPD</b>			
<b>Reaction to fire</b>	<b>Euroclass E</b>			
<b>Durability of reaction to fire against heat, atm, aging/degradation</b>	<b>There is no variation over time on the fire reaction properties of PU</b>			
<b>Sound absorption index</b>	<b>NPD</b>			
<b>Water absorption by immersion (28 days)</b>	<b>Declared level: WL(T)1</b> Absorption ≤ 1% vol.			
<b>Resistance to water vapor diffusion <math>\mu</math></b>	<b>Declared Level: Infinite MU</b> (thickness 20 – 160 mm)			
<b>Continuous combustion by incandescent</b>	European Test Method Under Development – Harmonized Standard European not yet available			
<b>Release of substances dangerous</b>	European Test Method Under Development – Harmonized Standard European not yet available			

Rev. 19/06/2024 Technical Office - 01.24

p. 2/2

**Cellino Attanasio, 1 December 2023**
**The legal representative:**
