

DECLARATION OF PERFORMANCE (DoP)

N° 1012-CPR-2013-07-01



1. Unique identification code of the product type:

POLIISO VV HD

**Polyisocyanurate (PIR) Panels – Polyiso foam with very high mechanical resistance
Foam between two saturated glass fleece supports**

 2. Intended use of the product: **Thermal insulation for construction**

3. Name and Address of the Manufacturer:

EDILTEC INSULATION S.p.A.
Z.I. CONTRADA STAMPALONE – 64036 – CELLINO ATTANASIO (TE)
Tel. 0861 668008 – Fax. 0861 669256

 4. System for the evaluation and verification of the constancy of performance: **System 3**

5. Notified Bodies:

ISTITUTO GIORDANO, Via Rossini, 2 – 47814 Bellaria (RN) – ITALY, NB 0407
CEIS S.L., carretera Villaviciosa de Odón in Móstoles Km 1.5 – 28935 Móstoles (Madrid) - SPAIN, NB 1722
TECNALIA, Area Anardi, 5 – E- 20730 Azpeitia (Guipuzkoa) – SPAIN, NB 1292

Notified testing laboratories (NB 0407 - NB 1722 - NB 1292) which have carried out type tests (ITT) for product groups according to characteristic.

❖ The performance of the product referred to in point 1 is in accordance with the performance declared in point 6.

❖ This declaration of performance is issued. under the sole responsibility of the manufacturer referred to in point 3.

6. Declared performance

Essential Feature	Performance	Harmonised Technical Specification
Thickness tolerance	Declared Class: T2 Thickness <50 mm : ± 2 mm Thickness 50 – 75 mm : ± 3 mm Thickness > 75 mm : -3/+5 mm	EN 13165:2016
Length and width tolerance	Size < 1000 mm : ± 5 mm Size from 1000 mm to 2000 mm : ± 7.5 mm Dimensions from 2001 mm to 4000 mm : ± 10 mm Size > 4000 mm : ± 15 mm	
Dimensional stability under specific temperature and humidity conditions	Declared Class: DS(70,90)4 At 70° C and 90% R.H.: Length-width change: ≤ 1% Thickness Change: ≤ 4%	

pag. 1/2


6. Declared service:

(N° 1012-CPR-2013-07-01)

Essential Features	Performance			Harmonised Technical Specification
Thermal Conductivity (λD) and Thermal Resistance (RD)	Thickness [mm]	λD: [W/mK]	RD: [m2K/W]	EN 13165:2016
	30	0,027	1,10	
	40	0,027	1,45	
	50	0,026	1,90	
	60	0,026	2,30	
	70	0,026	2,65	
	80	0,026	3,05	
	90	0,026	3,45	
	100	0,025	4,00	
	120	0,025	4,80	
	140	0,025	5,60	
Compressive strength with 10% crushing	Declared level: CS(10/Y)200 ≥ 200 kPa			EN 13165:2016
Perpendicular tensile strength	Declared level: TR 50 ≥ 50 kPa			
Reaction to fire	Euroclass E			
Durability of reaction to fire against heat, atm, aging/degradation	There is no variation over time on the fire reaction properties of PU			
Sound absorption index	NPD			
Determination of compressive viscous creep	NPD			
Water absorption by immersion (28 days)	Declared level: WL(T)2 Absorption ≤ 2% vol. (Thickness < 100 mm) Declared level: WL(T)1 Absorption ≤ 1% vol. (Thickness ≥ 100 mm)			
Resistance to water vapor diffusion μ	Declared level: MU 60 ±5 (thickness 30 – 140 mm)			
Continuous combustion by incandescent	European Test Method Under Development – Harmonized Standard European not yet available			
Release of substances dangerous	European Test Method Under Development – Harmonized Standard European not yet available			

p. 2/2

Cellino Attanasio, giugno 2026

The legal representative:

